

Skopos Fabrics Ltd

Providence Mills

Earlsheaton Dewsbury

West Yorkshire WF12 8HT

United Kingdom

T + 44 (0) 1924 465191

F + 44 (0) 1924 454575

E skopos@skopos.co.uk

www.skoposfabrics.com

Company Reg. No. 9702865

TECHNICAL SPECIFICATION

ORIGAMI COLLECTION

PROPERTY	STANDARD	MINIMUM SPECIFICATION REQUIRED
Composition	N/A	100% Trevira CS
Weight (g/m2)	(+/- 3%)	Akiri 210g, Engel 160g, Miura 202g, Oru 156g, Sonobe 310g, Tessel 185g
Width (cm)	(+/-2%)	+/- 2% Engel 305cm, Sonobe 310cm
	(. / 50/)	+/- 5% Akiri 140cm, Miura 292cm, Oru 140cm, Tessel
Constitutation	(+/-5%)	285cm (due to shrink yarn in weft)
Construction	N/A BS EN ISO 13934-1	Woven >300
Tensile Strength (N) Seam Slippage (mm)	BS EN ISO 13934-1	>300 <6
Martindale Pilling (cycles)	BS EN ISO 12945	4 at 2000 cycles
Wash Shrinkage	ISO 5077	<3% to care instructions
Colour Fastness to Water (grade)	BS EN ISO 105 E01	4
Colour Fastness to Light (grade)	BS EN ISO 105 B02	5
Colour Fastness to Washing to care	BS EN ISO 105 CO6	4
instructions (grade)	23 214 130 103 200	'
Colour Fastness to Dry Cleaning (grade	BS EN ISO 105 D01	4
Flammability	BS 5867 Part 2 Type C	Pass
	(Curtains & Drapes)	Dage
	BS7175 Section 3-Ignition source 0,1 & 5 (Bedspreads	Pass
	& Coverlets)	
	DIN 4102 Class B1	Pass
	NFP 92-503 Class M1	Pass
	UNI VF 8456 Italian Class	Pass
	Uno	, 333
	IMO Res A.471 (X11) IMO	Pass
	A563 (14) Curtains &	
	Drapes	
End Uses	Curtains, Bedcovers, Scatter cushions	
Cleaning/care Instructions		
	Do not bleach Low heat iron	
	Dry clean (sensitive conditions)	
	Do not tumble dry	
	Avoid any contact with bleach based cleaning agents as this can cause significant damage to the fabric.	
	Sunlight - although all our products achieve grade 5 or above light fastness when tested to BS EN ISO B02, it is prudent to avoid direct exposure to strong sunlight wherever possible as UV light can cause colours to fade and in extreme circumstances degradation of fabric. All curtains in this environment should be lined.	
	It is the contractor's resp passed onto the end user	onsibility to ensure all cleaning instructions are

