

TARANSAY – PRODUCT PERFORMANCE

PROPERTY	STANDARD	SPECIFICATION ACHIEVED
Composition	N/A	50% FR Recycled Polyester, 50% FR Polyester
Weight (g/m2)	(+/- 5%)	430gsm
Width (cm)	Flat measure	140cm
Fabric Type	N/A	Piece dyed
Tensile Strength (N)	BS EN ISO 13934-1	>600n
Tear Strength (N)	BS EN ISO 13937-3	>25n
Seam Slippage (mm)	BS EN ISO 13936-2	<4mm
Martindale Pilling (cycles)	BS EN ISO 12945-2	3/4
Dimensional Stability to Washing	BS EN ISO 6330:2012	<3%
Colour Fastness to Water (grade)	BS EN ISO 105 E01	4/5
Colour Fastness to Rubbing (grade)	BS EN ISO 105 X12	5
Colour Fastness to Light (grade)	BS EN ISO 105 B02	5
Colour Fastness to Washing to care instructions (grade)	BS EN ISO 105 C06	4/5
Colour Fastness to Dry Cleaning (grade)	BS EN ISO 105 D01	4/5
Flammability	BS5867 Part 2 Type B Curtains BS7175 Crib 5 Bedding IMO Part 7 (Drapes) IMO Part 9 (Bedding)	
End Uses	Curtains / Bed Throws / Cushions	
Cleaning instructions	Wash Label A 30 degree wash, 1 dot iron, dry clean sensitive conditions, do not bleach, do not tumble dry Before laundering curtains, always remove all curtain hooks and un-draw the heading tapes. Washing inside out will assist to reduce wear, maintain the original colour and ultimately increase the serviceable life of the product. Avoid any contact with bleach-based cleaning agents as this can cause significant damage to the fabric.	
Installation Instructions	<u>Usable width of fabric</u>	

APPSKD020A2 ISSUE 5 30 NOVEMBER 2022

SPECIALIST IN THE SUPPLY AND DESIGN
 OF FR FABRICS AND FURNISHINGS FOR
 THE INTERNATIONAL CONTRACT MARKET

	<p>Our fabric widths are quoted as the usable width only. The supplied fabric will be wider, incorporating the selvedge. This selvedge on either side of the fabric is finished to prevent unravelling and is often made of different and/or heavier threads than the woven fabric and sometimes in a different weave. The selvedge should be cut off and discarded and not used in the construction of your item. Incorporating the selvedge, even if only slightly, can lead to seam slippage over time.</p> <p><u>Sunlight Degradation to fabrics</u></p> <p>The process of sunlight fading fabrics is called photodegradation. This photodegradation breaks down the chemical bonds of dyes in fabrics fading them over time and, in turn, degrades the fabric itself. Prolonged exposure to sunlight will, in the long-term, make fabric brittle and accelerate disintegration. Bold colours are more prone to fading than lighter colours and fading will appear faster.</p> <p>It is widely recommended that for windows orientated such that they have a high exposure to sunlight (for example South facing windows, in the UK), UV reflective glazing is installed, or UV reflecting window film is installed where this is not practical.</p> <p>For window coverings, lining curtains is also an effective way to reduce the sunlight exposure onto face-fabrics, although it should be noted that the linings themselves will then absorb all light and are therefore likely to need replacing over time. Similarly, installing sheers will reflect an element of sunlight and allow occupants privacy in the room. Allowing extra width on tracks or poles allows the fabric to be pulled clear of the windows when curtains are open, preventing excessive sunlight exposure.</p> <p>It is the contractor's responsibility to ensure all cleaning and installation instructions are passed onto the end user.</p>
--	--