

## TARIM – PRODUCT PERFORMANCE

PROPERTY	STANDARD	SPECIFICATION ACHIEVED
Composition	N/A	100% FR Polyester
Weight ( g/m2 )	( +/- 5% )	150gsm
Width ( cm )	Flat measure	315cm
Fabric Type	N/A	Inherent Wide Width Woven Fabric With Slub Silk Effect
Seam Slippage (mm)	BS EN ISO 13936-2	<6
Martindale Pilling (cycles)	BS EN ISO 12945-2	4/5 at 2000 cycles
Wash Shrinkage	BS EN ISO 6330:2012	<3% to care instructions
Colour Fastness to Light (grade)	BS EN ISO 105 B02	5
Colour Fastness to Washing to care instructions (grade)	BS EN ISO 105 C06	5
Flammability	BS 5867 part 2 type B BS7175 IMO part 9	Pass Pass Pass
End Uses	Curtains, Bedding	
Cleaning instructions	Wash at 30°C Gentle Cycle Do not bleach Low Heat Iron Dry Clean (sensitive conditions) Do not tumble dry For more comprehensive care instructions refer also to Skopos Care & Stain Removal Guides available to download from Skopos website <a href="http://www.skoposfabrics.com">www.skoposfabrics.com</a>  Avoid any contact with bleach-based cleaning agents as this can cause significant damage to the fabric.	
Installation Instructions	<p><u>Sunlight Degradation to fabrics</u></p> <p>The process of sunlight fading fabrics is called photodegradation. This photodegradation breaks down the chemical bonds of dyes in fabrics fading them over time and, in turn, degrades the fabric itself. Prolonged exposure to sunlight will, in the long-term, make fabric brittle and accelerate disintegration. Bold colours are more prone to fading than lighter colours and fading will appear faster.</p> <p>It is widely recommended that for windows orientated such that they have a high exposure to sunlight (for example South facing windows, in the UK), UV reflective glazing is installed, or UV reflecting window film is installed where this is not practical.</p> <p>For window coverings, lining curtains is also an effective way to reduce the sunlight exposure onto face-fabrics, although it should be noted that the linings themselves</p>	

APPSKD020A2 ISSUE 4 April 2018

SPECIALIST IN THE SUPPLY AND DESIGN  
 OF FR FABRICS AND FURNISHINGS FOR  
 THE INTERNATIONAL CONTRACT MARKET

will then absorb all light and are therefore likely to need replacing over time. Similarly, installing sheers will reflect an element of sunlight and allow occupants privacy in the room. Allowing extra width on tracks or poles allows the fabric to be pulled clear of the windows when curtains are open, preventing excessive sunlight exposure.

It is the contractor's responsibility to ensure all cleaning and installation instructions are passed onto the end user.