

## TRANQUILITY ECO – PRODUCT PERFORMANCE

PROPERTY	STANDARD	SPECIFICATION ACHIEVED
Composition	N/A	50% Post Consumer Recycled Polyester / 50% Polyester FR with weighted selvedge
Weight ( g/m <sup>2</sup> )	(+/- 5%)	85
Width ( cm )	Flat measure (+/- 5%)	300
Fabric Type	N/A	Woven
Seam Slippage (mm)	BS EN ISO 13936-2	<6
Martindale Pilling (cycles)	BS EN ISO 12945-2	4 @ 2000 cycles
Wash Shrinkage	BS EN ISO 6330:2012	<3% to care instructions
Colour Fastness to Water (grade)	BS EN ISO 105 E01	>4
Colour Fastness to Rubbing (grade)	BS EN ISO 105 X12	>4
Colour Fastness to Light (grade)	BS EN ISO 105 B02	>4
Colour Fastness to Washing to care instructions (grade)	BS EN ISO 105 C06	>4
Colour Fastness to Dry Cleaning (grade)	BS EN ISO 105 D01	>4
Flammability	BS 5867 part 2 type B IMO FTPC PART 7	Pass Pass
End Uses	Curtains	
Cleaning instructions	Wash at 30°C Gentle Cycle Short spin Do not bleach Low Heat Iron (1 dot) Dry Clean (@ sensitive conditions) Do not tumble dry  Avoid any contact with bleach-based cleaning agents as this can cause significant damage to the fabric	
Installation Instructions	It is the contractor's responsibility to ensure all cleaning instructions are passed onto the end user	