

## TRANQUILITY – PRODUCT PERFORMANCE

PROPERTY	STANDARD	SPECIFICATION ACHIEVED
Composition	N/A	100% Polyester FR
Weight ( g/m2 )	(+/- 5% )	85
Width ( cm )	Flat measure (+/- 5%)	300
Fabric Type	N/A	Woven
Seam Slippage (mm)	BS EN ISO 13936-2	<6
Martindale Pilling (cycles)	BS EN ISO 12945-2	4 @ 2000 cycles
Wash Shrinkage	BS EN ISO 6330:2012	<3% to care instructions
Colour Fastness to Water (grade)	BS EN ISO 105 E01	>4
Colour Fastness to Rubbing (grade)	BS EN ISO 105 X12	>4
Colour Fastness to Light (grade)	BS EN ISO 105 B02	>4
Colour Fastness to Washing to care instructions (grade)	BS EN ISO 105 C06	>4
Flammability	BS 5867 part 2 type B	Pass
	IMO FTPC PART 7	Pass
End Uses	Curtains	
Cleaning/care instructions	<p>Wash at 30°C Gentle Cycle Short spin Do not bleach Low Heat Iron (1 dot) Dry Clean (® sensitive conditions) Do not tumble dry</p> <p>Before laundering curtains, always remove all curtain hooks and un-draw the heading tapes. Washing inside out will assist to reduce wear, maintain the original colour and ultimately increase the serviceable life of the product.</p> <p>Avoid any contact with bleach-based cleaning agents as this can cause significant damage to the fabric</p>	
Installation Instructions	It is the contractor's responsibility to ensure all cleaning instructions are passed onto the end user	